

Abstract

An injection assembly for an injection moulding machine, comprising a screw (2) mounted in a plasticising cylinder and an injection piston (8) which moves the screw (2) in the longitudinal direction and which is mounted in an injection cylinder, wherein there is provided a supply conduit for the injection cylinder having a control valve (13) which can be shut off and there is provided an additional conduit (14) which bypasses the control valve (13) and in which are arranged a device (17) for reducing the amount of the pressure fluid flowing to the injection cylinder (7) and possibly a device (16) for reducing the pressure.

(Figure 1)

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
1	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100